

# Elite Ultra-Matt-Technical Data & Specification Sheet

Contact Pristine Coatings on 01492 544777

**Product Name:** Elite Ultra Matt: Waterbased coating for the restoration of mineral-board suspended ceilings.

**Supplier:** Pristine Coatings, Unit 10 Phoenix Workshops, Station Rd, Mochdre, Colwyn Bay, LL28 5EF. Tel 01492 544777

**Description:** Elite Ultra-Matt is a premium quality coating for the restoration of suspended ceilings. It is designed to offer a perfectly flat matt finish with excellent light reflectance. When applied over acoustic ceiling tiles the acoustic properties & fire rating of the ceilings will remain intact.

**Where to Use:** Acoustic ceiling tiles, mineral-board tiles, plaster, and concrete. This coating is designed for interior ceiling applications the flat matt finish eliminates the low angular sheen often exhibited by regular emulsions.

## Properties:

- Ideal for suspended ceilings
- Waterbased
- Flat matt uniform finish
- Excellent productivity
- Non-Bridging (tiles will not stick to the grid system)
- B.S 476 Parts 6 & 7 (class '0' fire rating achieved)
- Vapour Permeable
- Will not flake or peel

## Specification

**Preparation:** Mask all light fittings, sprinkler heads & smoke detectors and tops of walls. Hang plastic sheeting down from tops of walls, continue the sheeting across floors & furniture until the area is totally protected from overspray. Brush down the surface to remove all dust, cobwebs etc & stainblock any waterstains.

## Application:

Apply by airless spray use a 0.15 tip, dilute by 5% and apply one full coat overlapping each pass by 50%. This should be sufficient. However depending on the substrate a further mist coat may be required to complete the project.

**Completion:** Clean machine with warm water, remove masking & clean area ready for re-occupation.

## Tech data:

Colour	White as standard but can be supplied in any RAL or BS colour
Solids	62%
Spread rate	8m <sup>2</sup> per litre depending on substrate.
Dry to touch	60 minutes
Recoat after	2 hours
Clean-up	Warm Soapy Water
Flash Point	100°C
WFT	up to 250 microns
Containers	20 litres
Weight	25 Kilos

